

10/577,210

1-30. (CANCELED)

31. (CURRENTLY AMENDED) An assembly (1, 30, 50) for activating first and second friction shifting elements (2, 3) by a pressure, the assembly comprising:

~~at least one of disc couplings and disc brakes positioned axially~~ ✓
~~adjacent each other and radially approximately on a transmission diameter in a~~ ✓
~~transmission, the transmission having first and second disc packets (8, 9), the first~~ ✓
~~friction shifting element (2) comprising a first disc packet (8) with a first servo device~~ ✓
~~(4) associated therewith and the second friction shifting element (3) comprising a~~ ✓
~~second disc packet (9) with a second servo device (5) associated therewith, and~~ ✓
~~each of the first and the second disc packets (8, 9) comprising inner discs (10, 11)~~ ✓
~~and outer discs (12, 13) secured to disc carriers (14, 15), and with which respective~~ ✓
~~first and second servo devices (4, 5) are associated and the first and second disc~~ ✓
~~packets (8, 9) being positioned axially adjacent each other within the transmission;~~ ✓

~~the inner discs (10, 11) of the first and the second friction shifting~~ ✓
~~elements (2, 3) disc packets (8, 9) are supported by a radially outwardly facing~~ ✓
~~surface of a common inner disc carrier (16);~~

~~the inner disc carrier (16) comprises a radial pot base (26) and a common~~
~~annular surface, connected with a periphery of the pot base (26), which supports the~~
~~inner discs (10, 11) of both the first and the second friction shifting elements (2, 3) disc~~ ✓
~~packets (8, 9) and the pot base (26) and the common annular surface form a pot-~~ ✓
~~shaped structure which is axially opened on one end;~~

~~the respective first and second servo devices (4, 5) are both located~~
~~primarily within a pot space (27) defined by the pot-shaped structure of the inner disc~~
~~carrier (16) as well as at least partially axially adjacent each other and radially inward~~ ✓
~~inward of the first and the second disc packets (8, 9) of the first and the second friction~~ ✓
~~shifting elements (2, 3);~~

~~the first friction shifting element (2) is located adjacent the pot base (26)~~
~~of the inner disc carrier (16);~~

12/1/08 8:53 AM

- 2 -

10/577,210

the first and the second friction shifting elements (2, 3) are activated individually and independent of each other by the respective first and second servo devices (4, 5); [[and]]

the ~~common~~ inner disc carrier (16), for both of the first and the second friction shifting elements (2, 3), has radial openings (21, 22, 23, 36, 37, 53, 58, 59) distributed on a circumference thereof in an axial area between both the disc packets (8, 9);

the inner discs (11) of the second disc packet (9) of the second friction shifting element (3) has axial openings (43) distributed on at least one of the circumference, and the inner disc carrier (16) has axially aligned recesses distributed on the circumference at least in the area of the second disc packet (9) of the second friction shifting element (3):

one of the openings (43) in the inner discs (11) of the second friction shifting element (3) or the recesses in the inner disc carrier (16) forms a penetration area through which axially aligned fingers (35) are guided, the axially aligned fingers are associated with the piston (6) of the first servo device (4) of the first friction shifting element (2); and

the axially aligned fingers (35) are provided to activate the first friction shifting element (2) and penetrate at least one of the openings (43) in the inner discs (11) of the second friction shifting element (3).

32. (PREVIOUSLY PRESENTED) The assembly according to claim 31, wherein each of the first and the second servo devices (4, 5) comprises an axially movable piston (6, 7) having one of:

a radially aligned pressure plate (20, 33, 34) whose radial free end facilitates engagement of one of the first and the second disc packets (8, 9) respectively associated with the first and the second servo devices (4, 5) upon activation of the respective first and the second servo devices (4, 5), and

several radially aligned fingers (19, 51, 52) positioned on the circumference thereof, and free ends of the several radially aligned fingers facilitates engagement of one of the first and the second disc packets (8, 9) respectively

12/01/08 4:53 AM

10/577,210

associated with the first and the second servo devices (4, 5) and the radially aligned fingers one of penetrate the radial openings (23, 53) of the inner disc carrier (16) or extend through the axially opened end of the inner disc carrier (16).

33. (PREVIOUSLY PRESENTED) The assembly according to claim 32, wherein the pressure plate (20, 33, 34) is ring-shaped.

34. (CANCELED)

35. (CURRENTLY AMENDED) The assembly according to claim [[31]] 56,
wherein the first servo device (4), associated with the first friction shifting element (2),
is located adjacent the pot base (26) and is positioned directly radially inwardly of the
first disc packet (8) of the first friction shifting element (2);

the first servo device (4) has on a piston (6), ~~several fingers distributed~~
~~about a circumference thereof~~, the ~~several~~ fingers which penetrate the radial openings
([[,]] 23, 53) of the inner disc carrier (16) in a radial direction and activate the first disc
packet (8) of the first friction shifting element (2) upon axial movement of the several
shift fingers in the direction [[of]] toward the pot base (26) of the inner disc carrier (16);

the second servo device (5), associated with a second friction shifting
element (3), is located directly radially inwardly of the second disc packet (9) of the
second friction shifting element (3); and

the second servo device (5), has on a piston (7), a pressure
plate (20) which extends through the axially opened end of the inner disc carrier (16)
for engaging the second disc packet (9) of the second friction shifting element (3) upon
activation of the second servo device (5).

36. (CANCELED)

37. (CURRENTLY AMENDED) The assembly according to claim [[36]] 31,
wherein at least one of the openings (43) and the axially aligned recesses in the inner
disc carrier (16) are constructed, when viewed in a direction of a circumference, as an
interruption of a disc entrainment profile on the inner disc carrier (16) and
correspondingly on the inner discs (11) of the second disc packet (9) spaced from the
pot base (26).

12/08 3:03 AM

- 4 -

10/577,210

38. (PREVIOUSLY PRESENTED) The assembly according to claim 36, wherein:

the first servo device (4) associated with the first friction shifting element (2) near the pot base (26) is positioned at least in part radially inwardly of the first disc packet (8) of the first friction shifting element (2) as well as in part radially inwardly of the disc second packet (9) of the second friction shifting element (3) spaced from the pot base (26);

the first servo device (4) has a pressure plate (33) on a piston (6), which extends through the axially opened end of the inner disc carrier (16) and is one of rigidly connected or action-connected at an outer diameter with the axially aligned fingers (35) which activate the first disc packet (8) of the first friction shifting element (2) upon moving via the axially aligned fingers (35) axially toward the pot base (26) of the inner disc carrier (16);

the second servo device (5) associated with the second friction shifting element (3), spaced from the pot base (26), axially borders the first servo device (4) and is positioned, at least in part, radially inwardly of the second disc packet (9) of the second friction shifting element (3) as well as, at least in part, radially below an axial section (31) of the piston (6) of the first servo device (4); and

the second servo device (5) has a pressure plate (34) on a piston which overlaps the pressure plate (33) of the piston (3) of the first servo device (4), outside the pot space (27) of the inner disc carrier (16), and activates the second disc packet (9) of the second friction shifting element (3) upon moving axially toward the pot base (26) of the inner disc carrier (16).

39. (CURRENTLY AMENDED) ~~The assembly according to claim 34, wherein~~
An assembly (1, 30, 50) for activating first and second friction shifting elements (2, 3)
by a pressure, the assembly comprising:

the first friction shifting element (2) comprising a first disc packet (8)
with a first servo device (4) associated therewith and the second friction shifting
element (3) comprising a second disc packet (9) with a second servo device (5)
associated therewith, and each of the first and the second disc packets (8, 9)

12/1/08 4:23 AM

- 5 -

10/577,210

comprising inner discs (10, 11) and outer discs (12, 13) secured to disc carriers (14, 15), and the first and second disc packets (8, 9) being positioned axially adjacent each other within the transmission;

the inner discs (10, 11) of the first and the second disc packets (8, 9) are supported by a radially outwardly facing surface of a common inner disc carrier (16);

the inner disc carrier (16) comprises a radial pot base (26) and a common annular surface, connected with a periphery of the pot base (26), which supports the inner discs (10, 11) of both the first and the second disc packets (8, 9) and the pot base (26) and the common annular surface form a pot-shaped structure which is axially opened on one end;

the respective first and second servo devices (4, 5) are both located primarily within a pot space (27) defined by the pot-shaped structure of the inner disc carrier (16) as well as at least partially axially adjacent each other and radially inward of the first and the second disc packets (8, 9) of the first and the second friction shifting elements (2, 3);

the first friction shifting element (2) is located adjacent the pot base (26) of the inner disc carrier (16);

the first and the second friction shifting elements (2, 3) are activated individually and independent of each other by the respective first and second servo devices (4, 5);

the common inner disc carrier (16), for both of the first and the second friction shifting elements (2, 3), has radial openings (21, 22, 23, 36, 37, 53, 58, 59) distributed on a circumference thereof in an axial area between both the disc packets (8, 9);

the first servo device (4) associated with the first friction shifting element (2) is at least primarily positioned radially inwardly of the first disc packet (8) of the first friction shifting element (2);

the second servo device (5) associated with the second friction shifting element (3) spaced from the pot base (26) is at least primarily positioned

12/08 4:53 AM

10/577.210

radially inwardly of the second disc packet (9) of the second friction shifting element (3);
and

both of the first and the second servo devices (4, 5) have several fingers (51, 52) distributed about a circumference of a respective piston (6, 7), and the several fingers (51, 52) penetrate in a radial direction, openings (53) provided in the common annular surface between both the first and the second disc packets (8, 9) and free ends of the several fingers (51, 52) ~~faciliate~~ facilitate engagement of the associated first and the second disc packet (8, 9),

the first friction shifting element (2) is engaged by a pulling activation of the piston (6) of the first servo device (4) via the several fingers (51) toward the pot base (26) of the inner disc carrier (16); and

the second friction shifting element (3) is engaged by a pressing activation of a piston (7) of the second servo device (5) away from the pot base (26) of the inner disc carrier (16).

40. (PREVIOUSLY PRESENTED) The assembly according to claim 39, wherein at least one finger (51) of the piston (6) of the first servo device (4) and at least one finger (52) of the piston (7) of the second servo device (5) are associated with each of the openings (53) radially distributed about the circumference in an axial area between the first and the second disc packets (8, 9).

41. (PREVIOUSLY PRESENTED) The assembly according to claim 39, wherein the several fingers (51, 52) of the pistons (6, 7) of both the first and the second servo devices (4, 5) are positioned, when spatially viewed, axially directly adjacent one another.

42. (PREVIOUSLY PRESENTED) The assembly according to claim 39, wherein the several fingers (51, 52) of the pistons (6, 7) of both the first and the second servo devices (4, 5) are positioned, when spatially viewed, axially interlaced in the direction of the circumference and in a same axial plane of the transmission.

43. (PREVIOUSLY PRESENTED) The assembly according to claim 39, wherein both of the pistons (6, 7) of the first and the second servo devices (4, 5) are axially positioned immediately adjacent one another.

12/1/08 4:33 AM

- 7 -

10/577,210

44. (PREVIOUSLY PRESENTED) The assembly according to claim 39, wherein at least one of the first servo device (4) and the second servo device (5) has a dynamic activation pressure compensation.

45. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein pressure compensation areas (17, 39, 56; 18, 40, 56), for the dynamic activation pressure compensation of the at least one of the first servo device (4) and the second servo device (5), are positioned axially adjacent to pressure areas of the at least one of the first servo device (4) and the second servo device (5).

46. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein a pressure compensation area (17, 39, 56) associated with the piston (6) of the first servo device is adjacent the pot base (26) of the inner disc carrier (16).

47. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein a pressure compensation area (18), associated with the piston (7) of the second servo device spaced from the pot base (26), is axially positioned between the piston (6) of the first servo device and the piston (7) of the second servo device.

48. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein a pressure compensation area (40, 57), associated with the piston (7) of the second servo device is located on a end of the piston (7) of the second servo device opposite the piston (6) of the first servo device.

49. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein a pressure compensation area (40, 57) of the second servo device (5) is positioned in the area of an axial edge of the inner disc carrier (16) spaced from the pot base (26).

50. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein pressure compensation areas (17, 39, 56; 18, 40, 56) associated with the pistons (6, 7) of the first and the second servo devices are positioned, when spatially viewed, either to one of axial left or an axial right of the pressure area which is associated with the pistons (6, 7) of the first and the second servo devices.

51. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein cooling oil is supplied to the inner and the outer discs (10, 12) of the first friction shifting element (2) which can flow from the pressure compensation area (17, 56) associated

12/01/08 4:33 AM

- 8 -

10/577,210

with the first friction shifting element (2) via a flow line (24, 54) that is constructed between a radial outer side of the pressure compensation area (17, 56) and a radial inner side of the inner disc carrier (16) and leads through the radial openings (21, 36, 58) in the inner disc carrier (16) which are positioned, when viewed spatially, in the area of the first disc packet (8) of the first friction shifting element (2).

52. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein cooling oil is supplied to the inner and the outer discs (11, 13) of the second friction shifting element (3) which can flow from the pressure compensation area (18, 57) associated with the second friction shifting element (3) via a flow line (25, 55) that is constructed between a radial outer side of this pressure compensation area (18, 57) and a radial inner side of the inner disc carrier (16) and leads through the radial openings (22, 37, 59) in the inner disc carrier (16) which are positioned, when viewed spatially, in the area of the second disc packet (9) of the second friction shifting element (3).

53. (PREVIOUSLY PRESENTED) The assembly according to claim 44, wherein cooling oil is supplied to the inner and outer discs (10, 12; 11, 13) of the first and the second friction shifting elements (2, 3), which can flow from the pressure compensation area (39) associated with the first friction shifting element (2) via a flow line (38) that is constructed between a radial outer side of the pressure compensation area (39) and the radial inner side of the inner disc carrier (16) and leads through the radial openings (36, 37) in the inner disc carrier (16) which are positioned, when spatially viewed, in the area of the first and the second disc packets (8, 9) of the first and the second friction shifting elements (2, 3).

54. (CANCELED)

55. (CURRENTLY AMENDED) The assembly according to claim [[31]] 56, wherein the inner discs (10, 11) of both the first and the second friction shifting elements (2, 3) are constructed as lining discs. ✓

56. (CURRENTLY AMENDED) An assembly (1, 30, 50) for activating first and second friction shifting elements (2, 3) by a pressure, the assembly comprising:

12/1/08 - 8:03 AM

- 9 -

10/577,210

~~at least one of disc couplings and disc brakes positioned axially~~ ✓
~~adjacent each other and radially approximately on a transmission diameter in a~~ ✓
~~transmission, the transmission having first and second disc packets (8, 9), the first~~ ✓
friction shifting element (2) comprising a first disc packet (8) with a first servo device ✓
(4) associated therewith and the second friction shifting element (3) comprising a ✓
second disc packet (9) with a second servo device (5) associated therewith, and ✓
~~each of the first and the second disc packets (8, 9) comprising inner discs (10, 11)~~ ✓
~~and outer discs (12, 13) secured to disc carriers (14, 15), and with which respective~~ ✓
~~first and second servo devices (4, 5) are associated and the first and second disc~~ ✓
packets (8, 9) being positioned axially adjacent each other within the transmission; ✓

~~the inner discs (10, 11) of the first and the second friction~~ ✓
~~shifting elements (2, 3) disc packets (8, 9) are supported by a radially outwardly~~ ✓
~~facing surface of a common inner disc carrier (16);~~

~~the inner disc carrier (16) comprises a radial pot base (26) and a common~~
~~annular surface, connected with a periphery of the pot base (26), which supports the~~
~~inner discs (10, 11) of both the first and the second friction shifting elements (2, 3) disc~~ ✓
packets (8, 9) and the pot base (26) and the common annular surface form a pot- ✓
~~shaped structure which is axially opened on one end thereof;~~

~~the respective first and second servo devices (4, 5) are both located~~
~~primarily within a pot space (27) defined by the pot-shaped structure of the inner disc~~
~~carrier (16) as well as at least partially partially axially adjacent each other and radially~~ ✓
~~inward of the first and the second disc packets (8, 9) of the first and the second friction~~
~~shifting elements (2, 3);~~

~~the first friction shifting element (2) disc packet (8) is located adjacent the~~ ✓
~~pot base (26) of the inner disc carrier (16);~~

~~the first and the second friction shifting elements (2, 3) are~~
~~activated individually and independent of each other by the respective first and second~~
~~servo devices (4, 5);~~

~~the common inner disc carrier (16), for both of the first and the~~
~~second friction shifting elements (2, 3) disc packets (8, 9), has radial openings (21, 22,~~ ✓

12/08 6:52 AM

10/577,210

23, 36, 37, 53, 58, 59) distributed on a circumference thereof in an axial area between both the disc packets (8, 9); and

the radial openings (23, 53) in the inner disc carrier (16), for accepting fingers (19, 51, 52), supported by at least one of the pistons (6, 7) of the first and the second servo devices (4, 5), are longer in the axial direction than an axial extent of the fingers (19, 51, 52) plus a gap of the first and the second disc packets (8, 9) of the associated first and the second friction shifting elements (2, 3).

57. (CURRENTLY AMENDED) The assembly according to claim [[31]] 56,
wherein each of the first and the second friction shifting elements (2, 3) is a disc coupling. ✓

58. (CURRENTLY AMENDED) The assembly according to claim [[31]] 56,
wherein both of the first and the second friction shifting elements (2, 3) are gear brakes in which a common inner disc carrier is connected, in a slip free manner, with one of the transmission housing, is integrated into the transmission housing, or in which the outer disc carrier is connected with the transmission housing or is integrated into the transmission housing. ✓

59. (CURRENTLY AMENDED) The assembly according to claim [[31]] 56,
wherein one of the first and the second friction shifting elements (2, 3) is a gear brake, in which an outer disc carrier is connected, in a slip free manner, with one of the transmission housing or is integrated into the transmission housing. ✓

12/1/08 2:14 AM